Technical Manual

RS 3000

Month

Reference Standard Series 2-Way

SPECIFICATIONS

ACOUSTIC & ELECTRICAL SPECIFICATIONS:

Nominal Impedance: 6 ohms

Power Rating: 20-100 watts RMSSensitivity: 89dB @ 1 watt, 1 meter

• Crossover Frequencies: 4,000Hz

• Frequency Response: 45Hz-22kHz +/-3dB

PRODUCTION HISTORY

- Introduced in 1988
- Discontinued 1990
- Original Retail Price: \$310.00/pair

PHYSICAL SPECIFICATIONS:

- 1x 1" (2.5cm) Polycell Tweeter
- 1x 8" (20.3cm) Polypropylene Woofer
- Dimensions: 20.75"H x 12"W" x 10.25"D

52.75cm(H) x 30.5cm(W) x 26cm(D)

Cabinet Not Sold
Grille #A026-261
Crossover #A015-262
Logo #716-8227-A

TECHNICAL INFORMATION **TWEETER** #902-2722 Substitute #902-4606 8" WOOFER TWEETER DIAPHRAGM #902-2666 #751-2873 C1 .33μF 100V R1 3.0Ω 5W 16" BLUE S/C L1 0.4mH C2 3.3μF 100V **TWEETER** SF/C 0000 16" BLU/BLK S/C \oplus L2 .45mH **INPUT** 0000 11" RED L/C СЗ 10μF 100V **WOOFER** R2 2.0Ω 15W 11" RED/BLK L/C